



Drilling Attachment | Product Range



Drilling attachments... for jobs in hard to reach locations



You can transform your excavator into a drill with the Montabert Micro CPA drill!

Application field :

- Blasting holes
- Trenches and road opening
- Utility works
- Rock bolting, draining, and tie back
- Rough terrain construction
- High reach drilling

Montabert drifters are well known for their:

- Increased performance
- Reliability
- Low maintenance costs

Montabert drills have intelsense controls that:

- Drill straight holes
- Great Efficiency
- Ease of utilization



MICRO CPA



MICRO CPA



MICRO CPA 360



CPA 225E



CPA X-TEND HC 109 RP



CPA X-TEND HC 150 RP



CPA X-TEND HC 150 RP



CPA X-TEND HC 170 RP

Technical Specifications

		MICRO CPA H22/H25	MICRO CPA R25/R32	MICRO CPA 360 R25/R32	CPA 225E	CPA 225ER	CPA X-TEND											
Drifter: Montabert		HC 20			HC 50		HC 109 RP			HC 150 RP				HC 170RP				
Rod Changer		No			No	Hydr: 1 Rod	No	Hydr: 1 Rod	Hydr: 7 Rod	No	Hydr: 1 Rod	Hydr: 7 Rod	No	Hydr: 1 Rod	Hydra: 4 Rod	No	Hydr: 1 Rod	Hydr: 4 Rod
First Rod Length	ft (m)	10 (3.0)		12 (3.7)	14 (4.3)		14 (4.3)				24 (7.3)							
	in	1-1 ³ / ₄	1 ¹ / ₄ -2 ³ / ₄	1 ³ / ₄ -2 ³ / ₄	1 ³ / ₈ -3	1 ³ / ₄ -3	2 ¹ / ₂ -4		3-5		3 ¹ / ₂ -5			3 ¹ / ₂ -6				
Hole Diameter	mm	26-45	32-71	45-71	36-76	45-76	64-102		76-127		89-127			89-155				
	ft (m)	19.7 (6.0)	29.5 (9.0)	29.5 (9.0)	39.4 (12)	49.2 (15)	11.5 (3.5)	24.6 (7.5)	95.1 (29)	11.5 (3.5)	24.6 (7.5)	95.1 (29)	21.7 (6.6)	44.9 (13.7)	101.7 (31)	21.7 (6.6)	44.9 (13.7)	101.7 (31)
Carrier Weight	T	5-10		8-15	15-25		22-30		25-33		22-30		25-33		25-35		30-40	
Type of Rod		INTEG STEEL HEX 22/25		R25/R32	T38		T45			T45/T51			T51					
Feed Swing		+/- 45		+/- 180	4 X 100		+/- 27											
Carrier Hydraulic Requirement	GPM (l/min)	14.5 (55)	17.2 (65)	18.5 (70)	37.0 (140)		47.6 (180)			51.5 (195)			51.5 (195)			55.5 (210)		
	PSI (Bar)	2321 (160)		2466 (170)	2321 (160)		2756 (190)			2828 (195)			2828 (195)			3046 (210)		
Type of Control		Radio Remote			Radio Remote		Electric Remote											
Drifter Control		"Intelsense 1"			"Intelsense E"		"Intelsense 2"											
Type of Centralizer		Man.	Man./Hyd	Hyd	Hydraulic		Hydraulic											
Dust Collector (Option)		Pneumatic			Hydraulic		Hydraulic											
Recommended Air Requirement	CFM	185			225		300	350	400	350	400	500	350	400	500	400	500	600
Weight	lb (kg)	1036 (470)	1124 (510)	1587 (720)	3197 (1450)	3483 (1580)	7253 (3290)	7474 (3390)	7915 (3590)	7297 (3310)	7518 (3410)	7959 (3610)	7540 (3420)	7760 (3520)	8201 (3720)	8091 (3670)	8311 (3770)	9039 (4100)



Montabert: an international presence in more than 100 countries. Optimize the performance of your demolition accessories by contacting our network which is designed to support our products. The Montabert network will provide you with expertise during implementation, maintenance with original spare parts, technical assistance and training.

Nothing contained in this brochure is intended to extend any warranty or representation expressed or implied, regarding the products described herein. Any such warranties or other terms and conditions of sale products shall be in accordance with Montabert's standard terms and conditions of sale for such products, which are available upon request. Specifications and machines can be modified at any time and without notice.



866.472.4373

2905 Shawnee Industrial Way Suwanee, GA 30024