



Plate Compactor | Product Range



Plate Compactor

Easily and safely compact soil, gravel, asphalt and aggregate in confined areas.

Versatile and efficient enough to drive sheet pile, post, and seawall.

Safer Than Hand-Held Compactors

- No need for a crew to work inside the trench

Standard Flow Control and Pressure Relieve Valves

- Standard on all models
- Prevents over speeding which leads to poor compaction and reduces bearing life

Direct Drive Heavy Duty Motor

- Provides ample power, maximum durability, and easy maintenance

Four Outboard Shock Mounts

- Distribute vibration evenly
- Improves compaction efficiency
- Extends component life

Flat Top Mount Design

- Allows the same plate compactor to be mounted to different carriers



	PCT34	PCT64	PCT114	PCT220
Recommended Carrier Weight	7,716 - 14,330 lb. (3.5 - 6.5 tons)	12,125 - 33,070 lb. (5.5 - 15 tons)	24,251 - 55,115 lb. (11 - 25 tons)	54,000 - 143,300 lb. (24.5 - 65 tons)
Operating Weight	478 lb. (217 kg)	856 lb. (388 kg)	1493 lb. (677 kg)	2687 lb. (1219 kg)
Flow Range	12 - 28 gpm (45 - 106 lpm)	12 - 28 gpm (45 - 106 lpm)	28 - 60 gpm (106 - 227 lpm)	42 - 70 gpm (159 - 265 lpm)
Dynamic Force	3400 lb. (1542 kg)	6400 lb. (2903 kg)	11350 lb. (5148 kg)	22000 lb. (9980 kg)
Frequency	2100 vpm	2000 vpm	2000 vpm	2100 vpm
Baseplate Size	18.75 in. x 26 in. (476 mm x 660 mm)	23.5 in. x 34.2 in. (597 mm x 869 mm)	26.75 in. x 38.5 in. (679 mm x 978 mm)	33.2 in. x 49.4 in. (843 mm x 1255 mm)
Height	17.3 in. (438 mm)	20.4 in. (517 mm)	27.0 in. (685 mm)	34.6 in. (880 mm)
Width	18.75 in. (476 mm)	23.5 in. (597 mm)	26.75 in. (679 mm)	33.2 in. (843 mm)
Length	26.0 in. (660 mm)	34.2 in. (869 mm)	38.5 in. (978 mm)	49.4 in. (1255 mm)



For more information visit: www.montabert.com

Email: ussales@montabert.com

Customer Service: 866-472-4373

Fax: 866-472-4950