MONTABERT

SILENT DEMOLITION

MONTABERT NEW SILENT DEMILITION TOOLS OFFERS A WIDE RANGE OF HIGH END QUALITY PRODUCTS. THEY ARE DESIGNED AND PRODUCED TO MEET AN EXCELLENT PRICE-PERFORMANCE RATIO AND LOW MAINTENANCE COSTS.

CUSTOMERS AND USERS FEEDBACKS ARE THE MAIN INNOVATION DRIVERS, TO IMPROVE USER EXEPRIENCE AND PERFORMANCES.

THE COMBINATION OF ULTRA RESISTANT STEELS AND TOP QUALITY COMPONENTS MAKES MONTABERT SILENT DEMOLITION TOOLS VERSATILE, EFFICIENT AND DURABLE ATTACHEMENTS.






HCG 7-250	HCG 10-300	HCG 10-400	HCG 15-400	HCG 20-500	HCG 20-600
5-10	7-15	7-15	10-17	13-20	14-22
517	737	770	930	1,120	1,170
1,450	1,840	1,840	1,670	1,720	1,720
770	600	770	750	850	1,050
250	290	390	380	500	600
2.7	4.0	4.0	5.6	5.1	5.1
350	350	350	350	350	350
60	70	70	80	80	80
25	25	25	25	25	25
140	140	140	90	90	90
	7-250 5-10 1.450 770 250 2.7 350 60 25	7-25010-3005-107-155177371,4501,8407706002502902.74.035035060702525	7-25010-30010-4005-107-157-155177377701.4501.8401.8407706007702502903902.74.04.0350350350607070252525	7-25010-30010-40015-4005-107-157-1510-175177377709301,4501.8401.8401.6707706007707502502903903802.74.04.05.63503503503506070708025252525	7-25010-30010-40015-40020-5005-107-157-1510-1713-205177377709301.1201.4501.8401.8401.6701.7207706007707508502502903903805002.74.04.05.65.135035035035035060707080802525252525

	HCG 7-250	HCG 10-300	HCG 10-400	HCG 15-400	HCG 20-500	HCG 20-600
Carrier weight (t)	5-10	7-15	7-15	10-17	13-20	14-22
Grab weight (kg)	517	737	770	930	1,120	1,170
Max jaw opening (mm)	1,450	1,840	1,840	1,670	1,720	1,720
Jaw width (mm)	770	600	770	750	850	1,050
Volume (I)	250	290	390	380	500	600
Closing force (t)	2.7	4.0	4.0	5.6	5.1	5.1
ening & closing (max bar)	350	350	350	350	350	350
Flow (I/min)	60	70	70	80	80	80
Rotation flow (I/min)	25	25	25	25	25	25
ation pressure (max bar)	140	140	140	90	90	90

	HCG 7-250	HCG 10-300	HCG 10-400	HCG 15-400	HCG 20-500	HCG 20-600
Carrier weight (t)	5-10	7-15	7-15	10-17	13-20	14-22
Grab weight (kg)	517	737	770	930	1,120	1,170
Max jaw opening (mm)	1,450	1,840	1,840	1,670	1,720	1,720
Jaw width (mm)	770	600	770	750	850	1,050
Volume (I)	250	290	390	380	500	600
Closing force (t)	2.7	4.O	4.0	5.6	5.1	5.1
Opening & closing (max bar)	350	350	350	350	350	350
Flow (I/min)	60	70	70	80	80	80
Rotation flow (I/min)	25	25	25	25	25	25
Rotation pressure (max bar)	140	140	140	90	90	90






	HCG 23-700	HCG 25-800	HCG 30-1000	HCG 32-1200	HCG 45-1500	HCG 75-2700
Carrier weight (t)	17-25	21-29	25-40	27-45	35-60	60-100
Grab weight (kg)	1,400	1,700	2,000	2,070	3,000	5,000
ax jaw opening (mm)	1.870	1,935	2,210	2,210	2,500	3.190
Jaw width (mm)	1.050	1,935	1,050	1.200	1.410	1,540
Volume (I)	700	800	1,000	1,200	1,410	2,900
Closing force (t)	5.3	6.3	6.5	6.5	9.1	17.3
g & closing (max bar)	350	350	350	350	350	350
Flow (I/min)	80	100	120	120	170	220-250
Rotation flow (I/min)	25	45	45	45	45	70
n pressure (max bar)	90	90	90	90	130	130

	HCG 23-700	HCG 25-800	HCG 30-1000	HCG 32-1200	HCG 45-1500	HCG 75-2700
Carrier weight (t)	17-25	21-29	25-40	27-45	35-60	60-100
Grab weight (kg)	1,400	1,700	2,000	2,070	3,000	5,000
Max jaw opening (mm)	1,870	1,935	2,210	2,210	2,500	3,190
Jaw width (mm)	1.050	1,050	1,050	1,200	1,410	1,540
Volume (I)	700	800	1,000	1,200	1,500	2,900
Closing force (t)	5.3	6.3	6.5	6.5	9.1	17.3
ening & closing (max bar)	350	350	350	350	350	350
Flow (I/min)	80	100	120	120	170	220-250
Rotation flow (I/min)	25	45	45	45	45	70
ation pressure (max bar)	90	90	90	90	130	130


	HCG 23-700	HCG 25-800	HCG 30-1000	HCG 32-1200	HCG 45-1500	HCG 75-2700
Carrier weight (t)	17-25	21-29	25-40	27-45	35-60	60-100
Grab weight (kg)	1,400	1,700	2,000	2,070	3,000	5,000
Max jaw opening (mm)	1,870	1,935	2,210	2,210	2,500	3,190
Jaw width (mm)	1.050	1,050	1,050	1,200	1,410	1,540
Volume (I)	700	800	1,000	1,200	1,500	2,900
Closing force (t)	5.3	6.3	6.5	6.5	9.1	17.3
Opening & closing (max bar)	350	350	350	350	350	350
Flow (I/min)	80	100	120	120	170	220-250
Rotation flow (I/min)	25	45	45	45	45	70
Rotation pressure (max bar)	90	90	90	90	130	130





				DCV	L G	
			_			
	HCG-U	HCG-U	HCG-U	HCG-U	HCG-U	HCG-U
360° ROTATION	7-200	10-300	17-450	23-550	25-700	32-900
DEMOLITION, LIGHT EXCAVATION & STONE SETTING PROJECTS Carrier weight (t)	5-10	7-17	14-25	20-27	21-35	27-45
& STORE SETTING PROJECTS	497	770	1,170	1,430	1,670	1,950
RUBBLE & RECYCLED Max jaw opening (mm)	1,445	1,846	1,783	2,142	2,170	2,397
	500	600	750	800	915	915
Volume (I)	190	290	450	550	700	970
ALL KINDS OF MATERIALS LOADING	2.7	4.1	4.7	5.7	6.3	6.7
LOADING HARDOX 400-450 JAWS Opening & closing (max bar)	350	350	350	350	350	350
Flow (I/min)	60	80	80	100	100	120
Rotation flow (I/min)	25	25	25	25	45	45
EXCHANGEABLE & TURNABLE Rotation pressure (max bar)	140	140	90	90	90	90
EXCHANGEABLE & TURNABLE HARDOX 500 BLADES						





CM-C 700	HCM-C 750	HCM-C 800
20-30	25-40	27–47
1,870	2,730	2,970
900	1,000	1,000
250	370	297
660	700	785
80-270	90-350	97-370
380	380	380
130-250	200-300	220-330
45	45	45
90	90	110
		-

MULTIPROCESSOR / MULTIFUNCTION JAW



FUNCTION JAW


HCM-M 700	HCM-M 750	HCM-M 800	HCM-M 900
20-30	25-40	30-47	40-65
2,070	2,700	3,370	4,370
650	720	770	830
510	570	605	650
575	625	700	827
83–270	95-350	105-370	125-400
380	380	380	380
130-250	200-300	220-330	300-400
45	45	45	45
90	90	110	110

MULTIPROCESSOR / SCRAP METAL JAW





ICM-S 650	HCM-S 700	HCM-S 800
15-24	20-30	27-47
1,400	1,830	2,870
427	470	560
187	217	258
370	450	540
87-270	100-270	130-370
350	380	380
130-250	130-250	220-330
45	45	45
90	90	110



HCP-R 850	HCP 1000	HCP-R 1000
15-27	20-40	20-40
1,890	2,320	2,730
830	950	950
470	560	560
850	950	950
270	310	310
100	125	125
175	225	225
350	350	350
130-220	180-260	180-260
25	_	45
90	_	90

SILENT DEMOLITION TOOLS









MONTABERT

MONTABERT, ENGINEERING & INNOVATION SINCE 1921







The use of innovative high performance technology in product design and manufacturing makes Montabert products the most efficient and reliable choice for customers around the globe. Since 1921, Montabert products have been produced with a commitment to designing methods and solutions focused on productivity, reliability and safety. A continuous investment in research and development has resulted in the delivery of technology products that will revolutionize the market. For almost 100 years, Montabert products have led the industry with three to five patents a year. With a network of 150 dealers around the world, you will always find a Montabert certified partner close to you to provide the best service and solutions.



The content of this brochure constitutes non-binding information and may be changed at any time without notice. Montabert gives, and the brochure contains, no warranties whatsoever, express or implied. All the contents, including but not limited to text, images, graphics are all subject to copyright and all intellectual property protection. Their use or misuse is strictly prohibited. Montabert trademark and logo used herein are the property of Montabert. Nothing contained on this document shall be construed as constituting any commitment by Montabert or as granting any license or right to use any intellectual property. ©2021 Montabert. All rights reserved.

montabert.com montabertusa.com